

# Installation Types

## Drop-In

Sits flush in grid system.

Fits all standard 2 ft. x 2 ft. grid systems with 9/16 and 15/16" wide rails.

Cross tees are available to convert 2' x 4' grid systems.

Simply paint suspended grid system to match tile color.

Our proprietary Drop-In Clips secure your tiles in place.

Acoustic version are micro perforated for superior sound quality.

## Nail-Up

Used on wood substrate.

Requires plywood, furring strips, or joists.

Original installation method used for 150 years.

## Snap Lock™

Used on plaster, drywall, cement or popcorn ceilings.

No plywood required.

Screws directly into drywall.

Each tile interlocks to the next using our patented flange system.

Leaves a nice butting seam and **no visible fasteners.**

## Acoustic

Creates the best ambiance for louder areas like restaurants, bars, offices, media rooms, etc.

Significantly reduces noise up to 85% when used in conjunction with an acoustical pad.

The echo-reducing perforations are so small, none of the design of the pattern is affected.

Available for Nail-Up and Drop-In installations.

## Backsplash

Original installation method used for 150 years.

Each panel contains a 1/4" nail rail that overlaps tight seams.

Apply to wall with an adhesive like Liquid Nails or a resin based ceramic tile adhesive like AcrylPro.